

- 100A
- MID Approved (for billing)
- Single Phase
- Surface Mounted
- Multi-Tariff version of the popular CM100LCD
- Commonly referred to as a dual-tariff, 2 rate, dual-rate, peak and off-peak meter, Economy 7 meter, or meter for night storage heaters.
- Anti-tamper version available (CM100LCD-2RATE-ETC)
- 5 Terminal version available for switching external loads (eg. night storage heaters) without the need for an additional time clock
- Din Rail version for fuse boards, mounting in an enclosure or installation IN harsh or external areas (DR2100-MF-2R)



Voltage Rating (U_n)	220-240V
Current Rating ($I_{min} - I_{ref} (I_{max})$)	0.25-5(100)A 0.5-10(100)A 0.75-15(100)A 1-20(100)A
Frequency (F_n)	50Hz
Active Accuracy Class (kWh)	A or B (kWh)
Type of circuit	1p2w
Temperature Range	-40°C to +70°C
Software/ Firmware Version No(s)	See list overleaf
Identification Location	LCD
Bill Of Materials Number(s)	See list overleaf
IP Rating	IP52
Insulation Protective Class	Class II
LED Pulse Constant	1000 imp/ kWh
Impulse Voltage Rating	8kV
AC Voltage Rating	4kV
Main Cover Sealing Type	Wire & Crimp x 1
Integrity of meter	Inaccessible without breaking seals
Intended Location of the Meter	Indoor
Type of Register	LCD

Remember to order your seals and wire.

Sealing the terminal cover ensures security and safety.

Sealing pliers also available.

